

Article 4 Nonattainment Area Rules; Dustproofing for Commercial Parking, Drives and Yards

4-4-130 Work Practice Standards

A. Commercial Unpaved Parking Lots

At any unpaved commercial parking lot other than a low-use unpaved commercial parking lot, the Owner and/or Operator shall:

1. Restrict vehicle access to only those areas for which control measures have been taken.
2. Dustproof the unpaved commercial parking lot with one of the following control measures:
 - a. Pave;
 - b. [Gravel surfacing] Uniformly apply and maintain surface gravel; or
 - c. [Dust suppressants & trackout control] Apply dust suppressants other than water and install, maintain, and use a suitable trackout control system that controls and prevents trackout and/or removes particulate matter from the tires and the exterior surfaces of motor vehicles that traverse the site.
3. Make a record of the dustproofing action taken.

B. Low-Use Unpaved Commercial Parking Lots

At any low-use unpaved commercial parking lot, the Owner and/or Operator shall:

1. Restrict vehicle access to only those areas for which control measures have been taken.
2. Dustproof the unpaved commercial parking lot with one of the following measures:
 - a. Pave;
 - b. [Gravel surfacing] Uniformly apply and maintain surface gravel;
 - c. [Dust suppressants & trackout control] Apply dust suppressants other than water and install, maintain, and use a suitable trackout control system that controls and prevents trackout and/or removes particulate matter from the tires and the exterior surfaces of motor vehicles that traverse the site; or
 - d. [Water & trackout control] Apply water and install, maintain, and use a suitable trackout control device that controls and prevents trackout and/or removes particulate matter from the tires and the exterior surfaces of motor vehicles that traverse the site.
3. Make a record of the dustproofing action taken.

Article 4 Nonattainment Area Rules; Dustproofing for Commercial Parking, Drives and Yards

4-4-130 Work Practice Standards continued

C. Compliance Determination

Implementation of the work practice standards required under this section shall be deemed inadequate until the Owner and/or Operator achieves compliance with the objective standards of §4-4-120.

D. Trackout Cleanup Requirement

If trackout occurs, the Owner and/or Operator shall:

1. Repair and/or replace the control measure(s);
2. Clean-up immediately such trackout from paved areas accessible to the public including curbs, gutters, and sidewalks when trackout exceeds a cumulative distance of 25 lineal feet;
3. Clean-up all visible trackout from paved areas accessible to the public at the end of the day.
4. Make a record of the repair, replacement and/or cleanup action taken.